

OFFICE: Digital colour and black & white laser printers

# bizhub C3100P

# bizhub 3301/4000/4700P



Fast, convenient and compact

- Mono/Colour
- Up to 31ppm A4



High productivity and versatility

- Black & white
- Up to 33/40/47ppm A4

## TECHNICAL SPECIFICATIONS

### PRINTER SPECIFICATIONS

<b>Copying process</b>	Electrostatic laser copy, tandem, indirect
<b>Toner system</b>	Simitri® HD polymerised toner
<b>Print speed A4</b>	Up to 31 ppm (mono/colour)
<b>Autoduplex speed A4</b>	Up to 31 ppm (mono/colour)
<b>1st copy out time</b>	12.9 sec. (mono/colour)
<b>Warm-up time</b>	Approx. 36 sec. <sup>2</sup>
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Page description language</b>	PCL5e/c, PostScript 3 (CPSI 3016), XPS <sup>1</sup>
<b>Operating systems</b>	Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 Windows Server 2012 (64) Windows Server 2012 R2 Macintosh OS X 10.x Linux Citrix
<b>Printer fonts</b>	80 PCL Latin, 137 PostScript 3 Emulation Latin
<b>Print functions</b>	Direct print <sup>1</sup> of PDF, JPEG, TIFF; XPS <sup>1</sup> and OOXML (DOCX; XLSX; PPTX); overlay; watermark; n-up
<b>Mobile Printing</b>	AirPrint (iOS), PageScope Mobile (iOS & Android)

### SYSTEM SPECIFICATIONS

<b>System memory</b>	1 GB (standard) 2 GB (optional)
<b>System hard disk</b>	320 GB (optional)
<b>Interface</b>	10-Base-T/100-Base-TX/1,000-Base-T Ethernet; USB 2.0
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
<b>Frame types</b>	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
<b>Printable paper size</b>	A6-A4; customised paper sizes
<b>Printable paper weight</b>	60-210 gsm
<b>Paper input capacity</b>	Standard: 350 sheets Max.: 850 sheets
<b>Tray 1</b>	250 sheets; A6-A4; 60-210 gsm
<b>Tray 2 (optional)</b>	500 sheets; A4; 60-90 gsm
<b>Manual bypass</b>	100 sheets; A6-A4; custom sizes; 60-210 gsm
<b>Automatic duplexing</b>	A4; 60-210 gsm
<b>Output capacity</b>	Max.: 200 sheets
<b>Copy/print volume</b>	Rec.: 6,500 pages (Monthly)
<b>Toner lifetime</b>	CMYK: 5,000 pages
<b>Imaging unit lifetime</b>	Black: 25,000 pages; CMY: 25,000 pages
<b>Power consumption</b>	220-240 V / 50/60 Hz Less than 1.2 kW (system)
<b>System dimensions</b>	447 x 544 x 350 mm
<b>System weight</b>	Approx. 24 kg

<sup>1</sup> HD-P06 optional hard disk enables secure printing, proof-then-print, print & hold, job storing, XPS emulation, F-Option support and ID card reader support

<sup>2</sup> Warm-up time may vary depending on the operating environment and usage

## TECHNICAL SPECIFICATIONS

### PRINTER SPECIFICATIONS

<b>Printing process</b>	Electrostatic laser
<b>Autoduplex speed A4</b>	Up to 14 ppm
<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Page description language</b>	PCL 5/6 PostScript 3, XPS
<b>Operating systems</b>	Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows 10 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2 Macintosh OS X 10.x Linux, Citrix
<b>Printer fonts</b>	89 PCL Latin 91 PostScript 3 Emulation Latin
<b>Print functions</b>	Duplex, n-up, watermark, electronic sorting
<b>Mobile Printing</b>	AirPrint (iOS), PageScope Mobile (iOS & Android)

### SYSTEM SPECIFICATIONS

<b>System memory</b>	128 MB (standard)
<b>Interface</b>	10-Base-T/100-Base-TX Ethernet USB 2.0, IEEE 1284 Bidirectional Parallel Wi-Fi 802.11b/g/n (optional)
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6); AppleTalk (EtherTalk); TCP; UDP
<b>Printable paper size</b>	A6-A4, customised paper sizes
<b>Printable paper weight</b>	60-163 gsm
<b>Paper input capacity</b>	Standard: 300 sheets Max.: 850 sheets
<b>Paper tray 1</b>	250 sheets, A6-A4, 60-90 gsm
<b>Paper tray 2 (optional)</b>	250 or 550 sheets, A5-A4, 60-120 gsm
<b>Manual bypass</b>	50 sheets, A6-A4, custom sizes, 60-163 gsm
<b>Automatic duplexing</b>	A4; 60-90 gsm
<b>Output capacity</b>	Max.: 150 sheets
<b>Print volume (monthly)</b>	Rec.: 3,600 pages
<b>Toner lifetime</b>	Up to 10,000 pages
<b>Imaging unit lifetime</b>	Up to 60,000 pages
<b>Power consumption</b>	220-240 V / 50/60 Hz Less than 520 W
<b>System dimensions</b>	399 x 382 x 263 mm
<b>System weight</b>	Approx. 14 kg