

PRODUCTION PRESSES: Colour Narrow Web Digital Label Press

# bizhub PRESS C71cf



The bizhub PRESS C71cf is ideal for label converters who are looking to shift volumes from conventional presses to digital – due to the reduction of print run lengths, request for faster delivery times, personalisation and versioning as well as production of on-demand runs. The bizhub PRESS C71cf offers outstanding productivity, brilliant image quality and a surprising ease of use: it is the perfect fit for new market expansion and complementary use with existing analogue machines.

- Colour narrow web digital label press
- 18.9m/per min on most commonly used self-adhesive materials

## ACCURIOPRO LABEL IMPOSE (OPTIONAL)

The application not only gives operators a simple and intuitive interface to automatically impose and prepare label jobs for printing. At the same time, the software also enables users to create PDFs as basis for the corresponding cutting tools on the die cutting equipment. Working seamlessly with the bizhub PRESS C71cf, AccurioPro Label Impose perfectly complements Konica Minolta's label press! AccurioPro Label Impose impresses with its PDF-based workflow, which also facilitates creating the correct data input for the creation of die tools, its VDP support, intuitive user interface and large print area of 320mm. Print providers cannot go wrong with the combination of the bizhub PRESS C71cf and AccurioPro Label Impose!

### TECHNICAL SPECIFICATIONS

#### SYSTEM SPECIFICATIONS

<b>Resolution</b>	1,200 x 1,200 dpi x 8 bit 1,200 x 3,600 dpi equivalent
<b>Paper width</b>	330 mm
<b>Max. printing image size</b>	1195 x 320 mm
<b>Printed image width</b>	Max. 320 mm
<b>Feeding speed (printing speed)</b>	18.9 m/min., 13.5 m/min., 9.45 m/min. Speed depends on the paper type (standard speed: 13.5 mm)
<b>Main unit dimensions (W x D x H)</b>	1,171 x 903 x 1,480 mm (operation unit included)
<b>Roll feeder/Roll winder (W x D x H)</b>	930 x 940 x 1,480 mm
<b>Main unit weight</b>	Main unit: 297 kg Main unit + Roll feeder/Roll winder: 949 kg (floor plate not included)

#### CONTROLLER

Internal Konica Minolta own controller IC-602

- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The actual life of each consumable will vary depending on use and other printing variables including coverage, size, media type, ambient temperature and humidity.
- Specifications are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged