

PRODUCTION PRESSES: Digital colour

# AccurioPrint C2060L



This production system launched under the new Accurio brand is targeted at small to mid-size commercial printers as well as in-house print rooms and Central Reprographic Departments (CRDs). As an entry-level printing system, it offers outstanding new features including scan and print to/from USB Flash, a dual colour highspeed scanner and the possibility to manage print jobs directly from the operating panel. CRDs will find it easy to adapt to changing document workflows in the company, enhance their overall productivity, and extend their range of products and services by offering new, sophisticated print products.

## Enhances overall productivity

- Colour SRA3+ digital press
- 61ppm A4
- 33ppm A3

## TECHNICAL SPECIFICATIONS

### SYSTEM SPECIFICATIONS

|                              |   |
|------------------------------|---|
| <b>Resolution</b>            | 1,200 x 1,200 dpi x 8 bit<br>1,200 x 3,600 dpi equivalent |
| <b>Paper weight</b>          | 62–300 gsm  |
| <b>Duplex unit</b>           | Non-stack type; 62–300 gsm                                |
| <b>Paper sizes</b>           | 330 x 487 mm; 330 x 1,200 mm (optional)                   |
| <b>Maximum image area</b>    | 323 x 480 mm  |
| <b>Paper input capacity</b>  | Standard: 1,500 sheets Max.: 4,250 sheets                 |
| <b>Paper output capacity</b> | Max.: 3,100 sheets  |
| <b>Main unit dimensions</b>  | 800 x 903 x 1,076 mm (W x D x H)                          |
| <b>Main unit weight</b>      | 316 kg  |

### PRODUCTIVITY

|                               |           |
|-------------------------------|-----------|
| AccurioPrint C2060L           |           |
| <b>SRA3 - max. per minute</b> | 31 ppm    |
| <b>A4 - max. per hour</b>     | 3,380 pph |
| <b>A3 - max. per hour</b>     | 1,792 pph |
| <b>SRA3 - max. per hour</b>   | 1,681 pph |

### CONTROLLER

|   |          |
|---|----------|
| <b>Internal Konica Minolta Controller</b> | IC-603 A |
| <b>Internal Fiery Controller</b>          | IC-417   |

### SCANNER SPECIFICATIONS

|                        |  |
|------------------------|--|
| <b>Scan speed A4</b>   | Up to 240 ipm  |
| <b>Scan modes</b>      | TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-eMail |
| <b>Scan formats</b>    | TIFF (single and multi page); PDF                                |
| <b>Scan resolution</b> | 600 x 600 dpi  |

### COPIER SPECIFICATIONS

|                        |                              |
|------------------------|------------------------------|
| <b>Gradations</b>      | 256 gradations               |
| <b>FCOT</b>            | Less than 8 sec. (colour A4) |
| <b>Magnification</b>   | 25–400%, in 0.1% steps       |
| <b>Multiple copies</b> | 1–9,999                      |

### ACCESSORIES

|  |          |
|--|----------|
| <b>Original cover</b>                    | OC-511   |
| <b>Automatic document feeder</b>         | DF-706   |
| <b>Working table</b>                     | WT-511   |
| <b>Heating unit for main body trays</b>  | HT-511   |
| <b>Heating unit for LU-202m/XL</b>       | HT-503   |
| <b>Bypass tray</b>                       | MB-506   |
| <b>Booklet finisher</b>                  | FS-612   |
| <b>Staple finisher</b>                   | FS-531   |
| <b>2/4-hole punch kit for FS-612/531</b> | PK-512   |
| <b>2-hole punch kit for FS-612/531</b>   | PK-513   |
| <b>Post inserter for FS-612/531</b>      | PI-502   |
| <b>Envelope fuser</b>                    | EF-103   |
| <b>Banner tray</b>                       | MK-740   |
| <b>Large capacity unit</b>               | LU-202m  |
| <b>Large capacity unit</b>               | LU-202XL |
| <b>Output tray</b>                       | OT-510   |
| <b>High capacity output tray</b>         | OT-511   |
| <b>Envelope feeding kit</b>              | MK-746   |