

OFFICE: Digital colour multifunctional devices

# bizhub C3110



- Mono/Colour
- Up to 31ppm A4

Delivers high quality and yet reduces print spend

## TECHNICAL SPECIFICATIONS

### SYSTEM SPECIFICATIONS

<b>System memory</b>	1 GB (standard) 2 GB (optional)
<b>System hard disk</b>	320 GB (optional)
<b>Interface</b>	10-Base-T/100-Base-TX/1,000-Base-T Ethernet; USB 2.0
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
<b>Frame types</b>	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
<b>Automatic document feeder</b>	Up to 50 originals; A6-A4; 50-110 gsm RADF
<b>Printable paper size</b>	A6-A4; customised paper sizes
<b>Printable paper weight</b>	60-210 gsm
<b>Paper input capacity</b>	Standard: 350 sheets Max.: 850 sheets
<b>Tray 1</b>	250 sheets; A6-A4; 60-210 gsm
<b>Tray 2 (optional)</b>	500 sheets; A4; 60-90 gsm
<b>Manual bypass</b>	100 sheets; A6-A4; custom sizes 60-210 gsm
<b>Automatic duplexing</b>	A4; 60-210 gsm
<b>Output capacity</b>	Max.: 150 sheets
<b>Copy/print volume (monthly)</b>	Rec.: 6,500 pages Max.: 120,000 pages
<b>Toner lifetime</b>	Black 5,000 pages; CMY 5,000 pages
<b>Imaging unit lifetime</b>	Black 25,000 pages; CMY 25,000 pages
<b>Power consumption</b>	220-240 V / 50/60 Hz Less than 1.2 kW (system)
<b>System dimensions</b>	447 x 544 x 500 mm (W x D x H)
<b>System weight</b>	Approx. 30 kg

### COPIER SPECIFICATIONS

<b>Copying process</b>	Electrostatic laser copy, tandem, indirect
<b>Toner system</b>	Simitri <sup>®</sup> HD polymerised toner
<b>Warm-up time</b>	Approx. 38 sec. <sup>3</sup>
<b>Copy resolution</b>	600 x 600 dpi
<b>Gradation</b>	256 gradations
<b>Multi-copy</b>	1-99
<b>Original format</b>	A6-A4
<b>Magnification</b>	25-400% in 1% steps; auto-zooming
<b>Copy functions</b>	Duplex copy; ID card copy; 2-in-1; 4-in-1; poster; density adjustments

### PRINTER SPECIFICATIONS

<b>Print resolution</b>	1,200 x 1,200 dpi
<b>Page description language</b>	PCL 5e/c PostScript 3 PDF 1.7 XPS <sup>1</sup>
<b>Operating systems</b>	Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003/2008 (32/64) Windows Server 2012 (64) Macintosh OS X 10.x Linux Citrix
<b>Printer fonts</b>	80 PCL Latin 137 PostScript 3 Latin
<b>Print functions</b>	Direct print <sup>4</sup> of TIFF, XPS <sup>1</sup> , PDF and JPEG; XPS <sup>1</sup> and OOXML (DOCX, XLSX, PPTX); secure print <sup>1</sup> ; combination; n-up; poster; overlay; watermark

### SCANNER SPECIFICATIONS

<b>Scan speed</b>	Up to 30 ipm (mono/colour)
<b>Scan resolution</b>	Max.: 600 x 600 dpi
<b>Scan modes</b>	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-USB Scan-to-HDD <sup>1</sup> Scan-to-DPWS Network TWAIN scan
<b>File formats</b>	TIFF; PDF; Compact PDF; JPEG; XPS <sup>1</sup>
<b>Scan destinations</b>	250 (shared with fax); LDAP support

### FAX SPECIFICATIONS

<b>Fax standard</b>	Super G3 (optional)
<b>Fax transmission</b>	Analogue PC-Fax
<b>Fax resolution</b>	Max.: 600 x 600 dpi (ultra-fine)
<b>Fax compression</b>	MH; MR; MMR; JBIG
<b>Fax modem</b>	Up to 33.6 Kbps
<b>Fax destinations</b>	250 (shared with scan); LDAP support
<b>Fax functions</b>	Polling; time shift; PC-Fax

<sup>1</sup> 1 HD-P06 optional hard disk enables secure printing, proof-then-print, print & hold, job storing, XPS emulation, i-Option support and ID card reader support

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed.

<sup>3</sup> Warm up time may vary depending on the operating environment and usage