PRODUCT SHOWCASE

OFFICE: Digital black & white multifunctional devices

bizhub 226



- Black & white
- Up to 22ppm

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System memory	128 MB
Interface	10Base-T/100Base-TX Ethernet (optional); USB 2.0;
and the second second	Wi-Fi 802.11b/g (optional)
Network protocols	TTCP/IP (IPv4; IPv6); HTTP; SNMP
Automatic document	Reverse type; up to 70 originals; A5-A3
feeder (optional)	35-128 gsm simplex; 50-128 gsm duplex
Printable paper size	A5-A3
Customised paper sizes	90-297 x 140-432 mm
Printable paper weight	64-157 gsm
Paper input capacity	Standard: 350 sheets Max.: 1,350 sheets
Paper tray 1	250 sheets; A5-A3;
	Customised paper sizes
	(90-297 x 140-432 mm);
	64-157 gsm
Multi-bypass tray	100 sheets; A5-A3;
1	Customised paper sizes
	(90-297 x 140-432 mm);
	64-157 gsm
Paper tray 2-5	250 sheets; 85-A3;
(optional)	Customised paper sizes
	(182-297 x 140-432 mm);
A STATISTICS	64-90 gsm
Automatic duplexing(opt)	v 45–A3; 64–90 gsm
Finishing modes	Group; sort; crisscross
Output capacity	Max.: 250 sheets
Copy/print volume	Rec.: 5,000 pages
(monthly)	Max.*: 15,000 pages
Toner lifetime	Up to 12,000 pages
Power consumption	220-240 V / 50/60 Hz; less than 1.3 kWh
System dimensions	607 x 570 x 458 mm (without options) (W x D x H)
System weight	28.2 kg (without options/consumables)
System weight	

Completes virtually all daily office jobs fast and reliably

Convina process	I sear electrostatic imega transfer
Copying process	Laser electrostatic image transfer
Toner system	Simitri® HD polymerised toner
Copy/print speed A4	Up to 22 ppm
	Up to 24 ppm (from optional paper tray)
Copy/print speed A3	Up to 8.0 ppm
Autoduplex speed A4 (optional)	Up to 15.8 ppm
1st copy out time	Less than 6.5 sec.
Warm-up time	Approx. 15 sec. ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multi-copy	1-999
Driginal format	A5-A3
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	2in1; 4in1; book copy; ID copy; shift margin; erase;
copy runctions	image rotation; program registration
PRINTER SPECIFICA	TIONS
Print resolution	GDI: 600 x 600 dpi
	PCL (optional): 1,200 x 600 dpi
Page description	GDI
language	PCL 6/5e (optional)
Operating systems	Windows Vista (32/64)
	Windows 7 (32/64)
	Windows 8 (32/64)
	Windows 10 (32/64)
	Windows Server 2008 (32/64)
	Windows Server 2008 B2
	Windows Server 2012
	Windows Server 2012 B2
	Linux: Citrix
Printer fonts	53 PCL Latin
Print functions	N-up; watermark; secure print; image rotation;
The functions	booklet function (optional)
SCANNER SPECIFIC	
Scan speed	Up to 46 opm (300 dpi via optional ADF)
(mono/colour)	Up to 20 opm (150 dpi via optional ADF)
Scan resolution	Max.: 600 x 600 dpi
	Scan-to-eMail (optional)
	Scan-to-eMail (optional) Scan-to-SMB (optional)
	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional)
	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB
	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional)
	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional)
Scan modes File formats	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF
Scan resolution Scan modes File formats Scan destinations	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional)
Scan modes File formats	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support
Scan modes File formats Scan destinations FAX SPECIFICATION:	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF: JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support
Scan modes File formats Scan destinations FAX SPECIFICATION: Fax standard	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional)
Scan modes File formats Scan destinations FAX SPECIFICATION: Fax standard	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue
Scan modes File formats Scan destinations FAX SPECIFICATION Fax standard Fax transmission	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue i-Fax
Scan modes File formats Scan destinations FAX SPECIFICATION: Fax standard	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue i-Fax Standard; Fine; Super-fine
Scan modes File formats Scan destinations FAX SPECIFICATION Fax standard Fax transmission	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue I-Fax Standard; Fine; Super-fine Max.: 408 x 392 dpi
Scan modes File formats Scan destinations FAX SPECIFICATION: Fax standard Fax transmission Fax resolution	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue I-Fax Standard; Fine; Super-fine Max.; 408 x 392 dpi (Super-fine via optional ADF)
Scan modes File formats Scan destinations FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; 250 speed dial destinations; S Super G3 (optional) Analogue I-Fax Standard; Fine; Super-fine Max.: 408 x 392 dpi (Super-fine via optional ADF) MH; MR; MMR; JBIG
Scan modes File formats Scan destinations FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression Fax modem	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue i-Fax Standard; Fine; Super-fine Max: 408 x 392 dpi (Super-fine via optional ADF) MH; MR; MBR; JBIG Up to 33.6 Kbps
Scan modes File formats Scan destinations FAX SPECIFICATION FAX standard Fax transmission Fax resolution Fax compression	Scan-to-eMail (optional) Scan-to-SMB (optional) Scan-to-FTP (optional) Scan-to-USB Local TWAIN scan Network TWAIN scan (optional) PDF; JPEG; TIFF 32 one-touch destinations; 250 speed dial destinations; LDAP support S Super G3 (optional) Analogue I-Fax Standard; Fine; Super-fine Max.: 408 x 392 dpi (Super-fine via optional ADF) MH; MR; MMR; JBIG

If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

* Warm-up time may vary depending on the operating environment and usage